

## RCP05 Plug-in socket receiver

The RCP05 plug-in socket receiver is simply inserted between the socket and the device that needs to be controlled.

After programming up to 32 Easywave transmitters, the device to be controlled can be switched on and off at will.

**Energy efficient:** The RCP05 consumes only 0.2 W in standby mode.




RCP05E5001-01-01K

### Technical specifications

Coding	Easywave Up to 32 transmitters can be programmed.
Frequency	868.30 MHz
Channels	1
Power supply	230 V AC, 50 Hz
Power consumption	0.2 W standby 0.8 W relay switched (without load)
Operating modes	ON/OFF (2-button operation) ON/OFF (1-button operation) TIMER (7 minutes, retriggerable)
Outputs	1 relay contact (normally open)
Maximum contact load	
D/A/NL/S/N und CH	10 A / 230 V AC
GB	13 A / 230 V AC
F/B/PL	16 A / 230 V AC
Operating temperature	-10 °C to +35 °C
Dimensions	50 x 120 x 75 mm
Color	white similar to RAL 9003

### Plug system



### Scope of delivery

- Plug-in socket receiver
- Operating manual

### Models

Product numbers	Description	Plug system
RCP05E5001-01-01K	Plug-in socket receiver 1-channel, white	D/A/NL/S/N
RCP05E5001-02-01K	Plug-in socket receiver 1-channel, white	GB
RCP05E5001-04-01K	Plug-in socket receiver 1-channel, white	F/B/PL
RCP05E5001-05-01K	Plug-in socket receiver 1-channel, white	CH