



Transmit



Receive



Decode



Control

Hand Transmitter RT24

The Hand Transmitter RT24 was designed for controlling shutters or awnings. In connection with the appropriate Easywave-Receiver and depending on the model the functions UP/STOP/DOWN or ON/OFF can be used.

The 4-channel-model of the RT24 offers the possibility to transmit a signal to all four channels at once (group-control) by pushing only one button.



RT24-5004E-01

Technical Details





Coding	factory coding with Easywave Telegram
Channels	1 or 4
Range	up to 150 m under favourable open field conditions
Power Supply	1x 3V battery, CR2032
Operation Indicator	1 respectively 4 LED's
Control	transmission lasts for as long as button is pressed (but max. 36 s)
Operation Modes	depending on the receiver; see model
Degree of Protection	IP54
Operating Temperatur	-20 °C to +60 °C
Dimensions	110 x 38 x 14 mm
Weight	37 g (including battery)

Scope of Delivery

- Hand Transmitter incl. battery
- Mounting Plate
- Mounting Accessories
- Operating Manual

Accessories (optional)

- Battery ACC-BAT-05



Models

Product Key	RT24-5001E-01	RT24-5004E-01	RT24-5001E-03	RT24-5004E-03
Frequency	868.30 MHz	868.30 MHz	868.30 MHz	868.30 MHz
Description	Hand Transmitter	Hand Transmitter	Hand Transmitter	Hand Transmitter
Operation Modes	UP/STOP/DOWN	4x UP/STOP/DOWN	ON/OFF	4x ON/OFF