

RTS13 Radio wall switch

The RTS13 wall switch is designed to be surface-mounted inside dry buildings.

The switch can be fitted to standard switch boxes or attached/screwed directly to a wall.

Depending on the model and the connected Easy-wave receiver, the RTS13 can be used to switch electrical devices on or off with a 1-button operation or to control roller shutters or awnings.




RTS13E5001-01-02K


Technical specifications

Coding	factory coding with Easywave telegram
Frequency	868.30 MHz
Channels	1 or 3
Range	typically 150 m in good free-field conditions
Power supply	1x 3V battery, CR2032
Operation	transmission lasts as long as the button is pressed (maximum 36 seconds)
Function	depends on the receiver (see models)
Operating temperature	-20 °C to +60 °C
Dimensions	80 x 80 x 10 mm
Weight	47 g (including battery)
Color	white similar to RAL 9003

Models



RTS13E5001-01-02K
1x UP/STOP/DOWN



RTS13E5003-01-02K
3x PULSE

Scope of delivery

- Wall switch
- Battery
- Mounting kit
- Operating manual

Models

Product numbers	Description	Function
RTS13E5001-01-02K	Radio wall switch 1-channel, white	1x UP/STOP/DOWN
RTS13E5003-01-02K	Radio wall switch 3-channel, white	3x PULSE