

RXP03 Plug-in socket repeater

The RXP03 plug-in socket repeater receives all radio telegrams from Easywave transmitters and retransmits them after a delay of approx. 0.3 seconds. As a result, the maximum range of a radio transmitter can be almost doubled.

Alternatively, it is possible to program up to 16 telegrams into the repeater. Only telegrams that have been programmed in can then simply be retransmitted.




RXP03E5001-01-01K

Technical specifications

Coding	Easywave Up to 16 transmitters can be programmed.
Frequency	868.30 MHz
Transmission delay	300 ms
Range	typically 150 m in good free-field conditions
Power supply	230 V AC, 50 Hz
Power consumption	0.7 W standby
Outputs	power outlet: country-specific plug system
Maximum contact load	mains voltage (not switchable): 10 A / 230 V AC
Operating temperature	-20 °C to +35 °C
Dimensions	50 x 120 x 75 mm
Color	white similar to RAL 9003

Plug system



Scope of delivery

- Plug-in socket repeater
- Operating manual

Models

Product numbers	Description	Plug system
RXP03E5001-01-01K	Plug-in socket repeater 1-channel, white	D/A/NL/S/N
RXP03E5001-02-01K	Plug-in socket repeater 1-channel, white	GB
RXP03E5001-04-01K	Plug-in socket repeater 1-channel, white	F/B/PL
RXP03E5001-05-01K	Plug-in socket repeater 1-channel, white	CH