

## RTC07 Wireless keypad

The RTC07 wireless keypad allows remote-controlled access by entering a 4-digit user pin.

3 pins can be created in total. Each pin can activate a separate receiver.

In addition, a temporary PIN can be generated for a user pin to allow temporary access for specific visitors or service providers. The temporary pin can be used three times.

An Easywave wireless receiver can be activated by the light button without entering a user pin.

The RTC07 has a battery control function which checks the batteries' capacity.



RTC07S5004A01-25K

### Technical specifications

Coding	factory coding with secwave telegram, AES 128-bit encryption Not compatible with Easywave products! Light button: Easywave code A, 1-button operation
Frequency	868.30 MHz
Channels	4
Range	typically 150 m in good free-field conditions
Power supply	2x batteries 1,5 V AAA
Operating indicator	LED
Operation	transmitter transmits, after PIN input, as long as the ENTER button is pressed (max. 36 seconds)
Function	depends on the receiver (see models)
Degree of protection	IP54
Operating temperature	-20 °C to +60 °C
Dimensions	80 x 115 x 33 mm
Weight	170 g (including batteries)
Color	white aluminum similar to RAL 9006

### Scope of delivery

- Wireless keypad
- Batteries
- Wall holder
- Mounting kit
- Operating manual

### Models

Product numbers	Description	Function
RTC07S5004A01-25K	Wireless keypad secwave 868 MHz aluminium finish with sliding lid	4x PULSE and 1x Easywave A